

UNIVERSITY OF TECHNOLOGY SYDNEY
Faculty of Engineering and Information Technology

**Exploring Centralized and Distributed Constraint
Propagation Algorithms for Solving Constraint
Satisfaction Problems**

by

Shufeng Kong

Dissertation directed by Professor Sanjiang Li

A THESIS SUBMITTED
IN PARTIAL FULFILLMENT OF THE
REQUIREMENTS FOR THE DEGREE

Doctor of Philosophy

Sydney, Australia

2018

Certificate of Authorship/Originality

I certify that the work in this thesis has not been previously submitted for a degree nor has it been submitted as a part of the requirements for other degree except as fully acknowledged within the text.

I also certify that this thesis has been written by me. Any help that I have received in my research and in the preparation of the thesis itself has been fully acknowledged. In addition, I certify that all information sources and literature used are quoted in the thesis.

Signature of student:

Production Note:

Signature removed prior to publication.

Dedication

To my beloved mom, Miaoping Deng, for raising me up and her unwavering support.

Acknowledgements

This thesis would not be possible without the help and contribution of many others. Most significantly, I am much indebted to my advisor, Professor Sanjiang Li, for his guidance and support throughout my PhD study. Sanjiang always paves the way for me and also his high standard and constructive criticisms have made me a better researcher and helped me grow as a person.

I am also grateful to my collaborators, Dr. Zhiguo Long, Dr. Jae Hee Lee and Dr. Michael Sioutis. Without their help, my thesis would not be as good as it is now. Zhiguo cheered me up when I was feeling depressed and tried his best to offer me help when I needed it. I learn a lot from Jae Hee about critical thinking and how to write a good research paper. He never just imposes his opinions on me but always tries to persuade me with right reasons.

I owe a great debt of gratitude to Professor Rina Dechter for her insightful ideas and wise advices when I was a visiting student at UC Irvine. Rina is very knowledgeable and far-sighted. She let me explore and pursue the questions I found of interest, but also provided direction when I needed it. It has been a pleasure and a privilege to work with her. I also want to thank the members of Rina's automated reasoning group, Junkyu Lee, Filjor Broka, Bobak Pezeshki and Qi Lou, for their warmest welcome and support when I stayed at UC Irvine.

Last but not least, I could not have done this without the incredible support of my family, especially, my beloved mom. She always believes in me even when I have doubts about myself.

Shufeng Kong
Sydney, Australia, 2018.

List of Publications

Journal Papers

- J-1. **Shufeng Kong**, Sanjiang Li, Yongming Li and Zhiguo Long: On tree-preserving constraints. *Annals of Mathematics and Artificial Intelligence*, 81(3-4): 241-271 (2017)
- J-2. **Shufeng Kong**, Sanjiang Li and Michale Sioutis: Exploring directional path-consistency for solving constraint networks. *The Computer Journal*, first online: 27 December 2017. doi: 10.1093/comjnl/bxx122
- J-3. **Shufeng Kong**, Jae Hee Lee and Sanjiang Li: A new distributed algorithm for efficient generalized arc-consistency propagation. *Autonomous Agent and Multi-Agent Systems*, first online: 10 May 2018. doi: 10.1007/s10458-018-9388-x

Conference Papers

- C-1. **Shufeng Kong**, Sanjiang Li, Yongming Li and Zhiguo Long: On tree-preserving constraints. In *Proceeding of the 21st International Conference on Principles and Practice of Constraint Programming (CP'15)*, pp. 244-261 (2015)
- C-2. **Shufeng Kong**, Jae Hee Lee and Sanjiang Li: A deterministic distributed algorithm for reasoning with connected row-convex constraints. In *Proceeding of the 16th International Conference on Autonomous Agent and Multiagent Systems (AAMAS'17)*, pp. 203-211 (2017)
- C-3. **Shufeng Kong**, Jae Hee Lee and Sanjiang Li: Multiagent simple temporal problem: the arc-consistency approach. In *Proceeding of the 32th AAAI Conference on Artificial Intelligence (AAAI'18)*, New Orleans, Louisiana, USA, February 2-7, 2018.

Contents

Certificate	ii
Dedication	iii
Acknowledgments	iv
List of Publications	v
List of Figures	x
List of Tables	xiv
Abbreviation	xv
Abstract	xvi
1 Introduction	1
1.1 Related Works	3
1.1.1 Local Consistency Algorithms for CSPs	3
1.1.2 Tractable Subclasses of CSPs	4
1.1.3 Local Consistency Algorithms for DisCSPs	6
1.2 Thesis Outline and Contributions	7
1.2.1 Tree-Preserving Constraints	7
1.2.2 CSPs Solvable with Directional PC	8
1.2.3 A Distributed Partial PC Algorithm for Solving CRC Constraint Networks	9
1.2.4 A Distributed AC Algorithm for Solving Multiagent STPs . .	10
1.2.5 A New Distributed Generalized AC Algorithm	11

1.3 Preliminaries	11
1.3.1 Constraint Satisfaction Problem	11
1.3.2 Local Consistency and Properties of Constraint Networks . . .	15
1.3.3 Triangulated Constraint Networks	17
1.3.4 Connected Row-Convex Constraint Networks	18
1.3.5 Algebraic Closure Properties of Constraints	20
2 Tree-Preserving Constraints	23
2.1 Contribution	23
2.2 Introduction and Chapter Outline	23
2.3 Preliminaries	27
2.4 Tree-Preserving Constraints	32
2.5 Partial PC for Tree-Preserving Constraints	38
2.6 The Scene Labelling Problem	47
2.7 Algebraic Closure Properties of Tree-Preserving Constraints	49
2.8 Evaluations	56
2.9 Conclusion	59
3 CSPs Solvable with Directional PC	70
3.1 Contribution	70
3.2 Introduction and Chapter Outline	71
3.3 Preliminaries	73
3.4 The Strong Directional PC Algorithm	75
3.5 Directional PC and Variable Elimination	76
3.6 Weak VEP Classes and Majority-Closed Classes	83
3.7 The Variable Elimination Algorithm DPC*	85

3.8	Evaluations	90
3.9	Conclusion	94
4	A Distributed Partial PC Algorithm for Solving CRC Constraint Networks	95
4.1	Contribution	95
4.2	Introduction and Chapter Outline	95
4.3	Preliminaries	98
4.4	An Efficient Centralized Algorithm for CRC Constraints	98
4.5	An Efficient Distributed Algorithm for CRC Constraints	107
4.6	Evaluations	111
4.6.1	Theoretical Comparisons	111
4.6.2	Experimental Comparisons	113
4.6.3	In-depth Evaluation of $D\Delta CRC$	114
4.7	Conclusion	115
5	A Distributed AC Algorithm for Solving Multiagent STPs	116
5.1	Contribution	116
5.2	Introduction and Chapter Outline	116
5.3	Preliminaries	118
5.4	Solving the STP with Arc-Consistency	121
5.4.1	A Centralized AC Algorithm for the STP	125
5.5	Solving the MaSTP with Arc-Consistency	128
5.6	Evaluation	132
5.6.1	ACSTP vs. P^3C	134

5.6.2	DisACSTP vs. D Δ PPC	135
5.7	Conclusion	136
6	A New Distributed Generalized AC Algorithm	137
6.1	Contribution	137
6.2	Introduction and Chapter Outline	137
6.3	Preliminaries	140
6.4	A New Distributed Arc-Consistency Algorithm	141
6.4.1	The Algorithm	144
6.4.2	Handling Termination	149
6.5	Analysis of DisAC3.1	154
6.5.1	Privacy of Individual Agents	154
6.5.2	Termination and Correctness	158
6.5.3	Time and Space Complexities	162
6.6	Non-binary Constraints	164
6.6.1	Generalized Arc-Consistency	164
6.6.2	A Distributed Generalized Arc-Consistency Algorithm	167
6.7	Evaluation	171
6.7.1	DisAC3.1 vs. DisAC9	173
6.7.2	DisGAC3.1 vs. GAC2001/3.1	178
6.8	Conclusion	178
7	Conclusion	183
7.1	Directions for Future Research	185
	Bibliography	187

List of Figures

1.1	A CSP example and its constraint graph.	13
1.2	A distributed binary CSP example: $V_i = \{v_1, v_2\}, C_i = \{R_{12}\},$ $V_j = \{v_3, v_4\}, C_j = \{R_{34}\}, V_w = \{v_7\}, V_p = \{v_6\}, V_k = \{v_5\},$ $V_q = \{v_8\}, V_l = \{v_9\}, C_{ij} = \{R_{23}, R_{24}\}, C_{ip} = \{R_{26}\}, C_{jk} = \{R_{45}\},$ $C_{wp} = \{R_{76}\}, C_{pk} = \{R_{65}\}, C_{kl} = \{R_{59}\}$ and $C_{kq} = \{R_{58}\}.$	14
1.3	Path-Consistency [13]	16
1.4	A graph $G = (V, E).$	18
1.5	A CRC constraint and a non-CRC constraint.	19
2.1	(a) A tree T . Subgraphs with node sets $\{a, b, c, d\}, \{a, b, c\},$ and $\{c, b, d\}$ form, respectively, a subtree, a chain, and a path of T . The degree of node b is 3 and the three branches of b are the subtrees with node sets $\{c\}, \{d\}$ and $\{a, e\}$ respectively. (b) A binary constraint R_{xy} between T_x and T_y , where a dashed arrow from a node u in T_x to a node v in T_y indicates that (u, v) is in R_{xy} . Node c is supported under R_{xy} with image $\{f, g, h\},$ and b is unsupported under $R_{xy}.$	28

2.2	(a) R_{xy} is a chain- but not path-preserving constraint as the the image of the path $\{c, b, d\}$ of T_x is $\{e, f, g, h\}$, which is not a path of T_y ; (b) R_{xy} is a path- but not chain-preserving constraint as the image of the chain $\{a, c\}$ of T_x is $\{e, f, g\}$, which is not a chain of T_y ; (c) R_{xy} is a tree-preserving but neither path- nor chain-preserving constraint as the image of the path $\{a, b\}$ of T_x , which is also a chain of T_x , is $\{e, f, g, h\}$ that is neither a path nor a chain of T_y . . .	29
2.3	M_{ab} is a trunk of tree T , i.e., the subtree induced by vertices with red colour.	34
2.4	The flow diagram of proof of Theorem 2.2.	35
2.5	A tree-preserving network $\mathcal{N} = \{R_{12}, R_{13}, R_{23}\}$ over forest domains F_1, F_2 , and F_3 , where each forest domain consists of three trees which contain only one node.	38
2.6	A triangulated graph G , where $\langle v_1, v_2, v_3, v_4, v_5 \rangle$ is a perfect vertex elimination ordering of G	39
2.7	Illustration of proof of Lemma 2.8. The figure is taken from [13]. . . .	40
2.8	Illustration of proof of Theorem 2.3.	42
2.9	Possible labelled line configurations of a junction in a picture and their corresponding forest structures.	48
2.10	A scene labelling instance and its corresponding constraint network. .	50
2.11	(a) R is a relation from tree domain T to T , and $R = \{(a, a), (b, a), (c, c)\}$. R is closed under the standard majority operation on T , but it is not tree-preserving w.r.t. T . (b) R is a relation from tree domain T to T , and $R = \{(a, a), (b, b), (c, b), (d, a)\}$. R is tree-preserving w.r.t. T , but it is not closed under the standard majority operation on T	51
2.12	Illustration of proof of proposition 2.8. Broken arrow lines indicate images of the node and empty circles indicates empty support nodes.	52

2.13	Performance evaluation of different local consistency algorithms for solving tree-preserving constraint networks with different densities. We set $n = 100$, $d = 30$ and $l = 0.5$	58
2.14	Illustration of proof of Lemma 2.7.	63
2.15	Possible configurations of two connected trunks $M_{a,b}$ and $M_{c,d}$, where $M_{a,b} \cup M_{c,d}$ is the whole tree in (c) and (d), a trunk in (a), (b) and (f), and a branch in (e).	66
2.16	Illustration of proof of Lemma 2.13.	67
3.1	A graph coloring problem with domain $D_i = \{red, blue\}$ for $i = 1, 2, 3, 4$ [37].	76
3.2	Two binary constraint networks \mathcal{N} and \mathcal{N}_{-4}	78
3.3	A constraint graph that is a chain.	78
3.4	An illustration of Example 3.3.	80
3.5	Illustration of proof of Theorem 3.2.	84
3.6	A constraint network \mathcal{N} and its elimination \mathcal{N}_{-w}	88
3.7	Performance comparisons among DPC* , SAC3-SDS and PC2001 for solving tree-preserving constraint networks.	91
3.8	Performance comparisons among DPC* , SAC3-SDS and PC2001 for solving random majority-closed constraint networks.	92
4.1	A constraint graph of Example 4.1.	96
4.2	Illustration of proof of Theorem 4.1.	104
4.3	Execution of DΔCRC on Example 4.1.	107
4.4	Performance comparisons between DΔCRC and D-CRC	112
4.5	Evaluation of our algorithm DΔCRC for different number of agents and network density. We set $n = 30$ and $d = 20$	114

5.1	An illustration of Example 5.1. Alice, Bob, company X , company Y are four agents, each owning a local simple temporal network. The circles represent variables and edges constraints. Red edges represent constraints that are shared by two different agents.	117
5.2	Evaluation of ACSTP and P ³ C. The y -axes (on the log scale) represent the number constraint checks.	133
5.3	Evaluation of DisACSTP and D Δ PPC. The y -axis (on the log scale) represent the number of NCCC's.	134
6.1	The standard agent communication graph of the distributed binary CSP in Figure 1.2.	143
6.2	A T-tree for the standard agent communication graph in Figure 6.1.	144
6.3	The relevant parts of variable v_2 of the distributed binary CSP in Figure 1.2.	147
6.4	Illustrations of messages flow.	150
6.5	Time lines of sending and receiving messages, where circles stand for the time points that agent i sends “domain update” messages to agent j , squares stand for the time points that agent j reports the latest received time stamps of “domain update” messages to the root agent via “up to date” messages, and triangles stand for the time points that the root agent receives “up to date” messages from agent j .	152
6.6	A ternary constraint (s, R) , where $s = (v_1, v_2, v_3)$ and $R = \{(a, c, e), (a, c, f), (b, d, f)\}$	165
6.7	Performance comparisons between DisAC3.1 and DisAC9 on random instances.	172
6.8	Number of messages sent by agents w.r.t. height of spanning trees. We set $n = 10, d = 10, \rho = 1.0, \beta = 0.5$ and $\#_{\text{agent}} = 10$	176
6.9	Speed-up vs. number of agents on benchmark problems.	177

List of Tables

3.1	Comparison of time complexities among state-of-the-art algorithms for solving majority-closed constraint networks.	90
6.1	Comparison of time and space complexities between DisAC3.1 and DisAC9.	173
6.2	Performance comparisons between DisAC3.1 and DisAC9 on the DOMINO problem. Note that m is the number of constraints and p is the number of agents used by both the algorithms.	174
6.3	Performance comparisons between DisAC3.1 and DisAC9 on the Radio Link Frequency Assignment Problem. Note that m is the number of constraints and p is the number of agents used by both the algorithms.	174

Abbreviation

(Dis)CSP - (Distributed) Constraint Satisfaction Problem

BCN - Binary Constraint Network

CRC - Connected Row-Convex

AC - Arc-Consistency

PC - Path-Consistency

DPC - Directional Path-Consistency

PPC - Partial Path-Consistency

STN - Simple Temporal Network

MaSTN - Multiagent Simple Temporal Network

ABSTRACT

Constraint propagation is central to the process of solving a constraint satisfaction problem (CSP). It can be used to solve several large tractable classes of CSPs directly and is also predominantly used to reduce the space of combinations that will be explored by a search algorithm. Constraint propagation, also known as local consistency enforcing, is the process of reducing domains of variables, strengthening constraints, or creating new ones. Arc-consistency (AC) and path-consistency (PC) are two well-known forms of local consistency. Designing efficient local consistency algorithms is a central research task in constraint processing. A related important question is to finding large tractable classes that can be solved by enforcing local consistency.

The class of connected row-convex (CRC) constraints defined over linear domains is a prominent tractable class which is a subclass of the class of row-convex constraints. While the class of row-convex constraints is intractable, it was shown that enforcing PC solves the CSPs over CRC constraints. The CRC constraint class is very expressive and can model problems in domains such as temporal reasoning, VLSI design, geometric reasoning, scene labelling as well as logical filtering.

In Chapter 2 we generalize the class of CRC constraints from linear domains to tree domains and obtain the new tractable class of tree-preserving constraints. We show that enforcing PC can transform a consistent tree-preserving constraint network into an equivalent globally consistent network. We also observe that CRC and tree-preserving constraint networks also can be solved by enforcing directional PC (DPC), a weaker form of PC which can be enforced more efficiently. A natural research question then is to characterize CSPs that are solvable with DPC. In Chapter 3 we provide such a characterization and prove that any class of majority-closed constraints is solvable with DPC and thus give a more efficient algorithm for solving these constraints.

In above, we assume that the knowledge about a CSP (i.e. domains and con-

straints) is known by one central agent, which is often not available when the knowledge about the problem is distributed among autonomous agents. Because of privacy reasons, simply collecting all such knowledge from the individual agents is undesirable or impossible. To address the issue, we need to develop distributed algorithms for solving distributed CSPs. We propose in Chapter 4 the first deterministic distributed algorithm to solve multiagent CRC constraint networks. Our algorithm is a distributed partial PC algorithm which can efficiently transform a CRC constraint network into an equivalent constraint network such that all constraints are minimal (i.e., they are the tightest constraints) and all solutions can be generated in a backtrack-free manner.

We then consider the class of simple temporal constraints in Chapter 5, which is closely related to the class of CRC constraints and is widely used in temporal planning and scheduling. In fact, discretized simple temporal constraints over finite domains are CRC constraints. Previous approaches focus on enforcing partial PC or directional PC to solve a simple temporal network (STN). We show that enforcing AC is sufficient to solve an STN, which not only provides a more efficient algorithm for STNs but also provides the first privacy-preserving distributed algorithm for solving multiagent STNs.

While the above algorithms are complete for certain tractable constraint classes, in Chapter 6 we propose a new distributed AC algorithm for general distributed CSPs, which is more efficient and leaks less private information of agents than existing ones. In particular, our new distributed AC algorithm uses a novel termination determination mechanism, which allows the agents to share domains, constraints and communication addresses only with relevant agents. We further extend it to the first distributed algorithm that enforces generalized AC (GAC) on k -ary ($k \geq 2$) distributed CSPs.